



## STERILISING SINKS

### DESCRIPTION

Sterilising sinks play a vital role in any commercial kitchen where utensils that are manually cleaned have to be sterilised to meet regulations.

The Stellex range is heavy duty and suitable for all catering and industrial kitchens. They are built around sturdy 30 x 30 stainless steel box section legs and framework, grade 430. Supplied with a stainless steel under top grade 304 and a stainless steel under shelf grade 430 to each end. Available with either a left hand or right hand steriliser bowl, size 760 x 510 x 380 mm deep with an adjacent wash bowl 300mm deep. Controlled and heated with a pre-fitted contactor and thermostat via a 6kw electric element, wireable for either single phase or 3 phase operation. Including a stainless steel valance panel to the front to conceal sink bowls and installation.

Top supplied as standard with a 60mm upstand and tile return to the rear and rear legs inset 100mm to clear pipework/services. Complete with gate valve fitted to steriliser bowl and upstand strainer assembly to wash bowl. Mounted on adjustable feet for easy levelling on site. Tops include 30mm diameter tap holes to fit most popular single and mixer taps. Specials available on request.



Sterilising sink

### FEATURES AND BENEFITS

#### Feature

- Stainless steel construction
- Satin brushed finish
- 1.5mm top
- 30x30mm box section legs & framework
- Fully integrated sink bowls
- Under shelf
- Adjustable feet
- 60mm upstand and tile return on wall standing units
- Rear legs inset 100mm on wall standing units
- 30mm tap holes
- Valance panel
- Pre-fitted heater and controls (single or 3 phase)

#### Benefit

- High quality stainless steel used throughout for corrosion resistance
- Offers a smooth easy to clean surface
- Heavy duty for strength and longevity
- Increased stability, weight bearing and strength
- Seamlessly welded to top for maximum hygiene
- Allows for easy cleaning & adaptability
- Easy levelling on site
- Protects walls
- Allows pipework/services
- Ease of installation
- Conceals services and improves appearance
- Easily wireable for either

### OPTIONS

- Different size sink bowls
- Left hand or right hand steriliser bowls
- Bespoke – please ask

### TECHNICAL DATA

#### Physical Sizes

##### Size

- Length (mm) 2400 / 3000
- Width (mm) 700
- Height (mm) 850

##### Electrical Requirements

- Voltage 240 V
- Frequency 50 Hz
- Normal Current 6 kW

Correct at time of going to press - Stellex reserves the right to change the specification

### STELLEX CONTACT DETAILS

Address: Stellex, Hadston Industrial Estate, Hadston,  
Morpeth, Northumberland, NE65 9YG

Tel: 01670 760082 - Email: sales@stellex.co.uk  
Web: www.stellex.co.uk